



# Mobile printer K329

Newly design / 2-3 inch / Portable / Class-leading

- Great looking design.
- Bluetooth 4.2 Low Energy and passive NFC tags for quick pair.
- Dual capabilities: Receipts & Labels
- Long-lasting battery and intelligent power consumption control for long work shifts.
- Compatible with multiple programming languages, reducing re-development.
- Visual editing apps, design at view, easy print.



Retails



Transportation



Manufacturing



Traffic Enforcement

# K329 Mobile Printer

## Specifications



### Printer Specifications

Print Method:Direct Thermal  
 Resolution:203dpi/8dots/mm  
 Maximum Print Width:72mm  
 Maximum Print Speed:up to 120mm/s



### Memory

RAM:8MB  
 FLASH:16MB



### Font

Bitmap fonts : ASCII(8\*16, 12\*24, 16\*32),  
 GBK(16\*16,24\*24, 32\*32)BIG 5(16\*16, 32\*32)  
 TTF fonts can be download



### Barcode symbologies

1D:Code 39, Code128, ITF, EAN-8,  
 EAN-13 etc.  
 2D:QRCode, PDF417, DataMatrix, etc



### Media Sensors

Gap, Blackmark,  
 Media out, Media cover open ,etc



### Buttons & Display

Power button,  
 Feed/Configure button;  
 LED Display



### Media Characteristics

Media width:42~80mm  
 Maximum Roll Outside Diameter:50mm  
 Media thickness:0.06~0.16mm  
 Media types:Direct Thermal



### Battery

Li-Ion 7.4V 2500mAh



### Communications

USB Type-C  
 Bluetooth 4.2 +2.1  
 2.4GHz&5GHz WIFI (optional)



### Programming Languages

TSPC, CPCL, ESC/POS, etc.



### Physical Characteristics

Dimension:118mm\*105mm\*62mm  
 Weight:450g



### Environmental

Operating Temperature:0~50°C(32~122°F)  
 Storage Temperature:-20~60°C(-4~140°F)  
 Operating Humidity:  
 20%~85% non-condensing  
 Drop Spec:1.5m tested over operating  
 temp range